



**Installation Instructions for:
Cable Hardware Kit**

Tools needed:

- 8' Ladders
- 5/16" Socket & Ratchet
- (2) – 9/16" Wrenches
- Pliers / Channel Locks

Installing Cables:

1. Un-spool and run cables the length of your cage.
2. Run one end of your cable through an extended turnbuckle and secure cable using a cable clamp. Tape the end of the cable to prevent fraying.

Note: If installing cables indoors attach the mounting plates to the walls at the a height that is approx. 8"-12" less than the height of your net and a width equal to the width of the net, if installing more than two cables space the others evenly between the outside plates. For maximum strength attach plates to poured concrete walls using anchor bolts or lug nuts.

If installing outdoors attach collar clamps to the end liner polls at the width of your net and space any center cables evenly between the outer cables.

3. Depending on hardware, hook or bolt turnbuckle onto wall-plate anchor tab (if installing indoors), or onto collar-clamp (if installing outdoors).
4. At opposite end install turnbuckle to wall plate or collar before attaching cable, be sure to extend the turnbuckle before installing.
5. Run cable through turnbuckle, pulling as much slack out of the cable as possible, and secure with cable clamp. Be sure to tape off the end of the cable to prevent fraying.
6. Tighten the turnbuckles on both sides to remove the remaining slack from the cable.

Note: You should provide for extra cable length when setting up initially. You can always cut off excess cable if it is not needed.

Attaching Net to the Cables:

1. The cables should be in place and tightened to your frame sections or walls.
2. Stretch out and position the net on the ground underneath the cables.

Tip: Attach snaps to border rope, including center rib-line(s), about every 2', while net is still on the ground. Twisting the rope helps the snap slide in. Snaps are designed to be snug to reduce friction & wear.

3. Starting on an end, on one of the outside lines (while on ladder or platform), have partner hand net to you. Attach the pre-loaded snaps around cable. Repeat this until one side is completed. Repeat for the middle and opposite side cables.

Tip: You can limit the number of trips up and down the ladder by bunching as much of the net on one end of the cable as possible – which will eventually "curtain" open to full length. Ladder should only need to be moved a few times for each line.

Complete. Swing away and enjoy!

